Specification Sheet for Product:
JennAir JDRP436HL
Stainless Steel 36 Inch Wide 5.1 Cu. Ft. Slide In Dual Fuel Range with Dual-Stacked PowerBurner and Halo-Effect Knobs

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

PRODUCT

	30" DUAL-FUEL RANGE	36" DUAL-FUEL RANGE
Overall Width (A)	29-7/8" (75.9 cm)	35-7/8" (91.1 cm)
Bullnose Height (B)	2-1/8" (5.4 cm)	2-1/8" (5.4 cm)
Control Panel Height (C)	7-1/2" (19.1 cm)	7-1/2" (19.1 cm)
Door Height (D)	20-11/16" (52.6 cm)	20-11/16" (52.6 cm)
Door Bottom to Handle Top: RISE™ (E)	20" (50.8 cm)	20" (50.8 cm)
Door Bottom to Handle Top: NOIR™ (E)	20-5/8" (52.4 cm)	20-5/8" (52.4 cm)
Toe-Kick Height (F)	6-11/16" (17 cm)	6-11/16" (17 cm)

FRONT VIEW

IMPORTANT: Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All JennAir® appliances are appropriately UL, CUL or CSA approved.

W11358022B

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

PRODUCT

	30" DUAL-FUEL RANGE	36" DUAL-FUEL RANGE
Depth with Control Panel Overhang (G)	27-11/16" (70.3 cm)	27-11/16" (70.3 cm)
Depth with Ha ndle: RISE™ (H)	29-13/16" (75.7 cm)	29-13/16" (75.7 cm)
Depth with Ha ndle: NOIR™ (H)	29-5/16 (74.5 cm)	29-5/16 (74.5 cm)
Depth with Door Fully Open (I)	46-1/2" (118.1 cm)	46-1/2" (118.1 cm)

TOP VIEW

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

PRODUCT

	30" DUAL-FUEL RANGE	36" DUAL-FUEL RANGE	48" DUAL-FUEL RANGE
Grates Top Height (A)	37-5/16" (94.8 cm)	37-5/16" (94.8 cm)	37-5/16" (94.8 cm)
Cooking Surface Top Height (B)	36" (91.4 cm)	36" (91.4 cm)	36" (91.4 cm)
Door Top Height (C)	27-13/16" (70.6 cm)	27-13/16" (70.6 cm)	27-13/16" (70.6 cm)
Handle Top Height: RISE™ (D)	27" (68.6 cm)	27" (68.6 cm)	27" (68.6 cm)
Handle Top Height: NOIR™ (D)	27-5/8" (70.2 cm)	27-5/8" (70.2 cm)	27-5/8" (70.2 cm)
Toe-Kick Height (E)	6-11/16" (17 cm)	6-11/16" (17 cm)	6-11/16" (17 cm)
	OPTIONAL ACCESSORIES		
Height to Top of 9" Stainless Steel Backsplash (F)	45" (114.3) min.	45" (114.3) min.	45" (114.3) min.

SIDE VIEW

IMPORTANT: Minimum height dimensions are at the lowest point of the height adjustment range. When the leveling legs are fully extended, all heights have 1-3/4" (4.4 cm) of added height.

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

PRODUCT

	30" DUAL-FUEL RANGE	36" DUAL-FUEL RANGE	48" DUAL-FUEL RANGE
Depth with Door Fully Open (G)	46-1/2" (118.1 cm)	46-1/2'' (118.1 cm)	46-1/2'' (118.1 cm)
Depth with RISE ™ Handle (H)	29-13/16" (75.7 cm)	29-13/16'' (75.7 cm)	29-13/16'' (75.7 cm)
Depth with NOIR ™ Handle (H)	29-5/16'' (74.5 cm)	29-5/16'' (74.5 cm)	29-5/16'' (74.5 cm)
Depth with Control Panel Overhang (I)	27-11/16'' (70.3 cm)	27-11/16'' (70.3 cm)	27-11/16" (70.3 cm)
Depth to Toe-Kick with Door (J)	26-3/8'' (67 cm)	26-3/8'' (67 cm)	26-3/8'' (67 cm)
Depth with RISE ™ Door (K)	27-1/4'' (69.2 cm)	27-1/4'' (69.2 cm)	27-1/4'' (69.2 cm)
Depth with NOIR ™ Door (K)	27-1/4'' (69.2 cm)	27-1/4'' (69.2 cm)	27-1/4'' (69.2 cm)

SIDE VIEW

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

PRODUCT

	48" DUAL-FUEL RANGE
Overall Width (A)	47-7/8" (121.6 cm)
Bullnose Height (B)	2-1/8" (5.4 cm)
Control Panel Height (C)	7-1/2" (19.1 cm)
Door Heights (D)	20-11/16" (52.5 cm)
Door Bottoms to Handle Tops: RISE™ (E)	20" (50.8 cm)
Door Bottoms to Handle Tops: NOIR™ (E)	20-5/8" (52.4 cm)
Secondary Oven Door Width (F)	17-3/4" (45.1 cm)
Main Oven Door Width (G)	29-5/8" (75.2 cm)
Toe-Kick Height (H)	6-11/16" (17 cm)

FRONT VIEW

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

PRODUCT

	48" DUAL-FUEL RANGE
Depth with Control Panel Overhang (I)	27-11/16" (70.3 cm)
Depth with Ha ndles: RISE™ (J)	29-13/16" (75.7 cm)
Depth with Ha ndles: NOIR™ (J)	29-5/16 (74.5 cm)
Depth with Doo rs Fully Open (K)	46-1/2" (118.1 cm)

TOP VIEW

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

OPENING AND CLEARANCE

	30" DUAL-FUEL RANGE	36" DUAL-FUEL RANGE	48" DUAL-FUEL RANGE
Combustible Area Above Cooking Surface Width (A)	30" (76.2 cm) min.	36" (91.4 cm) min.	48" (121.9 cm) min.
Bottom of Cabinet Height Above Cooking Surface (B)*	42" (106.7 cm) min.	58" (147.3 cm) min.	58" (147.3 cm) min.
Bottom of Cabinet Height Above Countertop (C)	18" (38.1 cm) min.	18" (45.7 cm) min.	18" (45.7 cm) min.
Distance to Fixed Wall or Combustible Material (D)	12" (30.5 cm) min.	12" (30.5 cm) min.	12" (30.5 cm) min.
Opening Width (E)	30" (76.2 cm) min.	36" (91.4 cm) min.	48" (121.9 cm) min.

*If installing a hood or hood liner above the range, follow the hood or hood liner instructions for dimensional clearances above the cooking surface.

FRONT VIEW

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

OPENING AND CLEARANCE

	30" DUAL-FUEL RANGE	36" DUAL-FUEL RANGE	48" DUAL-FUEL RANGE
Upper Cabinet Depth (F)	13" (33 cm) max.	13" (33 cm) max.	13" (33 cm) max.
Depth to Wall (G)*	1-1/2" (3.8 cm) min.	1-1/2" (3.8 cm) min.	1-1/2" (3.8 cm) min.

*If the back wall is constructed of a combustible material and a backsplash is not installed, a 1-1/2" (3.8 cm) minimum clearance is required.

SIDE VIEW

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

ELECTRICAL REQUIREMENTS

	30" DUAL-FUEL RANGE	36" DUAL-FUEL RANGE	48" DUAL-FUEL RANGE
Electrical Zone Width (A)	22" (55.9 cm)	28" (71.1 cm)	40" (101.6 cm)
Electrical Zone Height (B)	15" (38.1 cm)	15" (38.1 cm)	15" (38.1 cm)
Electrical Zone Depth (C)	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)

ELECTRIC REQUIREMENTS CHECKLIST

- ☐ A 240 volt, 60 Hz, fused, grounded circuit is required.
- ☐ For 30" and 36" ranges, use a 40-amp circuit.
- ☐ For 48" ranges, use a 50-amp circuit.
- ☐ A dedicated circuit is recommended.

RECOMMENDED ELECTRICAL ZONE

WIDTH TO ELECTRICAL CONDUIT

? IF YOU HAVE QUESTIONS ABOUT YOUR ELECTRICAL SUPPLY, CALL A LICENSED, QUALIFIED ELECTRICIAN.

DIMENSIONS

JENNAIR® DUAL-FUEL RANGES

GAS REQUIREMENTS

	30" CONNECTED DUAL-FUEL RANGE	36" CONNECTED DUAL-FUEL RANGE	48" DUAL-FUEL RANGE
Gas Opening Width (A)	6" (15.2 cm)	14" (35.6 cm)	24" (61 cm)
Gas Opening Height (B)	3" (7.6 cm)	3" (7.6 cm)	3" (7.6 cm)
Gas Opening Depth (C)	5" (12.7 cm)	5" (12.7 cm)	5" (12.7 cm)
Distance from Side Cabinet to Gas Opening (D)	6" (15.2 cm)	6" (15.2 cm)	6" (15.2 cm)
Width to Gas Inlet (E)	12-3/4" (32.4 cm)	12-3/4" (32.4 cm)	12-3/4" (32.4 cm)

RECOMMENDED GAS ZONE

FRONT VIEW

WIDTH TO GAS INLET

BACK VIEW

? IF YOU HAVE QUESTIONS ABOUT YOUR GAS SUPPLY, CALL A LICENSED, QUALIFIED SERVICE TECHNICIAN.

®/™ ©2019 JennAir. All rights reserved.

Specification Sheet for Product:
JennAir JXL6536HSS
Stainless Steel 36 Inch Wide Built-In Range Hood Liner - Blower Sold Separately

36" CUSTOM HOOD LINER

JXL6536H

Signature Features

CUSTOM HOOD LINER

This hidden ventilation system mounts to the inside of a custom-built vent covering that can blend into the kitchen's design or be highlighted as a visual feature of the kitchen.

OPTIONAL 600 CFM OR 1,200 CFM INTERNAL BLOWER

Three-speed blower – ordered separately – rapidly rids the air of smoke, steam and cooking odors so the air is fresh and clean.

OPTIONAL 1,200 CFM IN-LINE BLOWER

Quickly removes smoke, steam and cooking odors from the kitchen and mounts further down the duct run to help reduce the noise of the ventilation system in the kitchen.

Feature Listing

VENTILATION FEATURES

Optional 600 CFM or 1,200 CFM Internal Blower

Optional 1,200 CFM In-Line Blower

10-Inch Round Exterior Venting

Dishwasher-Safe Stainless Steel Baffle Filters

CONTROL FEATURES

Knob Controls

Three Fan Speed Settings

Auto Sense Option

Two Lighting Levels

DESIGN FEATURES

Custom Hood Liner

Versatile Installation Options

Halogen Task Lighting

OPTIONAL ACCESSORIES

1,200 CFM In-Line Blower – UXI1200DYS

1,200 CFM Internal Blower – UXB1200DYS

600 CFM Internal Blower – UXB0600DYS

Make-Up Air Kit – W10446917

Dishwasher-Safe Stainless Steel Baffle Filter – W10351855A

Spacer Kit (48") – W10646269

Spacer Kit (42") – W10646268

Stainless Steel Backsplash with Two Shelves (48") – W10285449

Stainless Steel Backsplash with Two Shelves (36") – W10285448

Specifications

Shipping Weight (lbs) 51

Volts 120

Amps 15

Dimensions

Overall Dimensions 35(7/8)" x 11(1/2)" x 22"

Do not make any cutouts based on this information

Style Options

STAINLESS STEEL DESIGN

JXL6536HS

LIMITED WARRANTY

Bold = Top Features

JENNAIR®

®/™ © 2019 JennAir. All rights reserved. Specifications subject to change without notice.

Specification Sheet for Product:
JennAir JMC6224HL
Stainless Steel RISE 24 Inch Wide 1.4 Cu. Ft. 3400 Watt Electric Speed Oven with JennAir Connect

DETAILED PLANNING DIMENSIONS

JENNAIR® SMALL SPEED OVEN

JMC6224HM – 23 7/16" X 18 5/16" X 24" (Depth With Handle)

JMC6224HL – 23 7/16" X 18 5/16" X 24 5/8" (Depth With Handle)

PRODUCT DIMENSIONS

FRONT VIEW

TOP VIEW

MODEL #		**JMC6224HM**		**JMC6224HL**	
		in	cm	in	cm
A	Overall width	23 7/16	59.5	23 7/16	59.5
B	Height of control panel	3 1/8	8	3 1/8	8
C	Space between control panel and door	3/16	0.4	3/16	0.4
D	Height to top of handle	13 1/8	33.3	13 1/8	33.3
E	Height of door	14	35.6	14	35.6
F	Overall height	18 5/16	46.5	18 5/16	46.5
G	Height of trim	3/8	1	3/8	1
H	Width of recessed oven	21 15/16	55.8	21 15/16	55.8
I	Depth of recessed oven	21 1/16	53.4	21 1/16	53.4
J	Depth with door	21 7/8	55.6	21 7/8	55.6
K	Depth with handle	24	61	24 5/8	62.6
L	Depth with door fully open	35 3/16	89.3	35 3/16	89.3

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All JennAir® appliances are appropriately UL, CUL or CSA approved.

JENNAIR®

DETAILED PLANNING DIMENSIONS

JENNAIR® SMALL SPEED OVEN

JMC6224HM – 23 7/16" X 18 5/16" X 24" (Depth With Handle)
JMC6224HL – 23 7/16" X 18 5/16" X 24 5/8" (Depth With Handle)

DIMENSIONS AS INSTALLED

SIDE VIEW

MODEL #		JMC6224HM		JMC6224HL	
		in	cm	in	cm
A	Height to top of handle	13 3/16	33.4	13 3/16	33.4
B	Height to trim extending below cutout	3/8	1	3/8	1
C	Height from top of recessed oven to top of control panel	3/8	1	3/8	1
D	Height from bottom of recessed oven foot to bottom of oven vent	3/8	1	3/8	1
E	Height of recessed oven	17 9/16	44.6	17 9/16	44.6
F	Height to top of control panel	17 15/16	45.6	17 15/16	45.6
G	Depth with door fully open	35 3/16	89.3	35 3/16	89.3
H	Depth with handle	24	61	24 5/8	62.6
I	Depth with door	21 7/8	55.6	21 7/8	55.6
J	Depth of recessed oven	21 1/16	53.4	21 1/16	53.4

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All JennAir® appliances are appropriately UL, CUL or CSA approved.

JENNAIR®

JENNAIR® SMALL SPEED OVEN - STANDARD INSTALLATION

JMC6224HM – 23 7/16" X 18 5/16" X 24" (Depth With Handle)
JMC6224HL – 23 7/16" X 18 5/16" X 24 5/8" (Depth With Handle)

OPENING/ CLEARANCE DIMENSIONS

FRONT VIEW **SIDE VIEW**

MODEL #		JMC6224HM JMC6224HL	
		in	cm
A	Width of cabinet (min.)	23 5/8	60
B	Width of cutout	21 15/16	55.8
C*	Height of cutout (recommended)	17 3/4	45
D	Top of cutout to bottom of upper cabinet door (min.)	1/2	1.2
E	Bottom of cutout to top of lower cabinet door (min.)	1/2	1.2
F**	Bottom of cutout to floor (min.)	36 9/16	92.8
G	Depth of cutout (min.)	21 1/16	53.5
H	Top of cutout to underside of countertop (min.)	1/2	1.2
I	Bottom of cutout to floor	1/2	1.2
e	Recommended junction box location		

*Will fit cutout height from 17 9/16" (44.6 cm) to 17 15/16" (45.6 cm)

Minimum dimension **only for Canada market

ELECTRICAL REQUIREMENTS
208 V or 240 V, 60 Hz, 20 A fused, grounded circuit is required. A dedicated circuit is required.

The length of conduit provided is for serviceability. Do not cut the conduit. The junction box should be located 3" (7.6 cm) maximum below the support surface. Drill a 1" (2.5 cm) minimum diameter hole in the right rear or left rear corner of the support surface for access to the junction box.

NOTE: For under counter installation, the junction box should be located in the adjacent right or left cabinet. Drill a 1" (2.5 cm) minimum diameter hole in an upper corner of the side wall for access to the junction box.

UNDER COUNTER INSTALLATION
(without cooktop installed above)

BACK VIEW

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All JennAir® appliances are appropriately UL, CUL or CSA approved.

JENNAIR®

JENNAIR® SMALL SPEED OVEN - FLUSH INSTALLATION

JMC6224HM – 23 7/16" X 18 5/16" X 21 7/8" (Depth Without Handle)
JMC6224HL – 23 7/16" X 18 5/16" X 21 7/8" (Depth Without Handle)

OPENING/ CLEARANCE DIMENSIONS

FRONT VIEW

SIDE VIEW

MODEL #		**JMC6224HM JMC6224HL**	
		in	cm
A	Width of flush inset cutout (min.)	23 11/16	60.2
B	Width of opening (min.)	22	55.9
C	Height of flush inset cutout (min.)	19 9/16	47.2
D	Height of opening (min.)	18 1/4	46.4
E**	Bottom of cutout to floor	36 1/16	91.6
F	Depth of cutout (min.)	21 7/8	55.6
e	Recommended junction box location		

Minimum dimension **only for Canada market.

ELECTRICAL REQUIREMENTS
208 V or 240 V, 60 Hz, 20 A fused, grounded circuit is required. A dedicated circuit is required.

The length of conduit provided is for serviceability. Do not cut the conduit. The junction box should be located 3" (7.6 cm) maximum below the support surface. Drill a 1" (3.4 cm) minimum diameter hole in the right rear or left rear corner of the support surface for access to the junction box.

NOTE: For under counter installation, the junction box should be located in the adjacent right or left cabinet. Drill a 1" (2.5 cm) minimum diameter hole in an upper corner of the side wall for access to the junction box.

FLUSH INSTALLATION REQUIREMENTS
A 21 7/8" (55.6 cm) minimum cutout depth is required. These dimensions will result in a 1/8" (0.3 cm) reveal on the top, a 1/8" (0.3 cm) reveal on the sides and a 1/8" (0.3 cm) reveal on the bottom of the wall oven.
The front face of the cleats and spacers will be visible and should be treated as a finished surface.

CABINET REQUIREMENTS
NOTE: When using under counter installation, check cabinet manufacturer's specifications to verify fit.

UNDER COUNTER INSTALLATION
(without cooktop installed above)

TOP VIEW

BACK VIEW

*Cleats and spacers must be recessed 13/16" (2.1 cm) from the front of the cabinet.

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All JennAir® appliances are appropriately UL, CUL or CSA approved.

®/™ ©2019 JennAir. All rights reserved. Used under license in Canada.

DIMENSIONS DE PLANIFICATION DÉTAILLÉES

PETIT FOUR À CUISSON RAPIDE JENNAIR®

JMC6224HM – 23 7/16" X 18 5/16" X 24" (profondeur avec poignée)
JMC6224HL – 23 7/16" X 18 5/16" X 24 5/8" (profondeur avec poignée)

DIMENSIONS DU PRODUIT

VUE AVANT

VUE DU DESSUS

Nº DE MODÈLE		**JMC6224HM**		**JMC6224HL**	
		po	cm	po	cm
A	Largeur totale	23 7/16	59,5	23 7/16	59,5
B	Hauteur du tableau de commande	3 1/8	8	3 1/8	8
C	Espace entre le tableau de commande et la porte	3/16	0,4	3/16	0,4
D	Hauteur jusqu'au sommet de la poignée	13 1/8	33,3	13 1/8	33,3
E	Hauteur de la porte	14	35,6	14	35,6
F	Hauteur totale	18 5/16	46,5	18 5/16	46,5
G	Hauteur de la garniture	3/8	1	3/8	1
H	Largeur du four encastré	21 15/16	55,8	21 15/16	55,8
I	Profondeur du four encastré	21 1/16	53,4	21 1/16	53,4
J	Profondeur avec porte	21 7/8	55,6	21 7/8	55,6
K	Profondeur avec poignée	24	61	24 5/8	62,6
L	Profondeur avec porte complètement ouverte	35 3/16	89,3	35 3/16	89,3

IMPORTANT : Les spécifications dimensionnelles sont fournies uniquement à des fins de planification.
Ne faire aucune découpe sur la base de cette information. Se référer au Guide d'installation avant de choisir une armoire, de vérifier les connexions électriques/gaz, d'effectuer des découpes ou de commencer l'installation.
Tous les appareils JennAir® sont homologués UL, CUL ou CSA.

JENNAIR®

DIMENSIONS DE PLANIFICATION DÉTAILLÉES

PETIT FOUR À CUISSON RAPIDE JENNAIR®

JMC6224HM – 23 7/16" X 18 5/16" X 24" (profondeur avec poignée)
JMC6224HL – 23 7/16" X 18 5/16" X 24 5/8" (profondeur avec poignée)

DIMENSIONS À L'INSTALLATION

VUE LATÉRALE

Nº DE MODÈLE		**JMC6224HM**		**JMC6224HL**	
		po	cm	po	cm
A	Hauteur jusqu'au sommet de la poignée	13 3/16	33,4	13 3/16	33,4
B	Hauteur jusqu'à la garniture en dessous de l'ouverture	3/8	1	3/8	1
C	Hauteur du haut du four encastré jusqu'au haut du tableau de commande	3/8	1	3/8	1
D	Hauteur du bas du pied du four encastré jusqu'au bas de l'évent du four	3/8	1	3/8	1
E	Hauteur du four encastré	17 9/16	44,6	17 9/16	44,6
F	Hauteur jusqu'au haut du tableau de commande	17 15/16	45,6	17 15/16	45,6
G	Profondeur avec porte complètement ouverte	35 3/16	89,3	35 3/16	89,3
H	Profondeur avec poignée	24	61	24 5/8	62,6
I	Profondeur avec porte	21 7/8	55,6	21 7/8	55,6
J	Profondeur du four encastré	21 1/16	53,4	21 1/16	53,4

IMPORTANT : Les spécifications dimensionnelles sont fournies uniquement à des fins de planification.
Ne faire aucune découpe sur la base de cette information. Se référer au Guide d'installation avant de choisir une armoire, de vérifier les connexions électriques/gaz, d'effectuer des découpes ou de commencer l'installation.
Tous les appareils JennAir® sont homologués UL, CUL ou CSA.

JENNAIR®

DIMENSIONS DE PLANIFICATION DÉTAILLÉES

PETIT FOUR À CUISSON RAPIDE – INSTALLATION STANDARD JENNAIR®

JMC6224HM – 23 7/16" X 18 5/16" X 24" (profondeur avec poignée)
JMC6224HL – 23 7/16" X 18 5/16" X 24 5/8" (profondeur avec poignée)

DIMENSIONS D'OUVERTURE ET DE DÉGAGEMENT

VUE AVANT

VUE LATÉRALE

Nº DE MODÈLE		**JMC6224HM JMC6224HL**	
		po	cm
A	Largeur minimale de l'armoire	23 5/8	60
B	Largeur de l'ouverture	21 15/16	55,8
C*	Hauteur de l'ouverture (recommandée)	17 3/4	45
D	Distance minimale du haut de l'ouverture jusqu'au bas de la porte de l'armoire supérieure	1/2	1,2
E	Distance minimale du bas de l'ouverture jusqu'au haut de la porte de l'armoire inférieure	1/2	1,2
F**	Distance minimale du bas de l'ouverture jusqu'au sol	36 9/16	92,8
G	Profondeur minimale de l'ouverture	21 1/16	53,5
H	Distance minimale du haut de l'ouverture jusqu'au-dessous du comptoir	1/2	1,2
I	Distance du bas de l'ouverture jusqu'au sol	1/2	1,2
e	Emplacement recommandé pour la boîte de jonction		

*Convient à une ouverture avec hauteur comprise entre 17 9/16" (44,6 cm) et 17 15/16" (45,6 cm)

Dimension minimale **uniquement pour le marché canadien

EXIGENCES ÉLECTRIQUES
Un circuit mis à la terre de 208 V ou 240 V, 60 Hz avec fusible de 20 A est requis. Un circuit dédié est requis.

La longueur du conduit fournie est destinée à faciliter l'entretien du four. Ne pas couper le conduit. La boîte de jonction doit être située à 3" (7,6 cm) maximum sous la surface de support. Percer un trou de diamètre minimal de 1" (2,5 cm) dans le coin arrière droit ou arrière gauche de la surface de support pour accéder à la boîte de jonction.

REMARQUE : Pour une installation sous le comptoir, la boîte de jonction doit être située dans l'armoire adjacente droite ou gauche. Percer un trou de diamètre minimal de 1" (2,5 cm) dans un coin supérieur de la paroi latérale pour accéder à la boîte de jonction.

INSTALLATION SOUS COMPTOIR
(sans table de cuisson au-dessus)

VUE ARRIÈRE

IMPORTANT : Les spécifications dimensionnelles sont fournies uniquement à des fins de planification.
Ne faire aucune découpe sur la base de cette information. Se référer au guide d'installation avant de choisir une armoire, de vérifier les connexions électriques/gaz, d'effectuer des découpes ou de commencer l'installation.
Tous les appareils JennAir® sont homologués UL, CUL ou CSA.

JENNAIR®

PETIT FOUR À CUISSON RAPIDE – INSTALLATION EN AFFLEUREMENT JENNAIR®

JMC6224HM – 23 7/16" X 18 5/16" X 21 7/8" (profondeur sans poignée)
JMC6224HL – 23 7/16" X 18 5/16" X 21 7/8" (profondeur sans poignée)

DIMENSIONS D'OUVERTURE ET DE DÉGAGEMENT

VUE AVANT **VUE LATÉRALE**

Nº DE MODÈLE		JMC6224HM JMC6224HL	
		po	cm
A	Largeur minimale de l'ouverture intégrée en affleurement	23 11/16	60,2
B	Largeur minimale de l'ouverture	22	55,9
C	Hauteur minimale de l'ouverture intégrée en affleurement	19 9/16	47,2
D	Hauteur minimale de l'ouverture	18 1/4	46,4
E**	Distance du bas de l'ouverture jusqu'au sol	36 1/16	91,6
F	Profondeur minimale de l'ouverture	21 7/8	55,6
e	Emplacement recommandé pour la boîte de jonction		

Dimension minimale **uniquement pour le marché canadien

EXIGENCES ÉLECTRIQUES
Un circuit mis à la terre de 208 V ou 240 V, 60 Hz avec fusible de 20 A est requis. Un circuit dédié est requis.

La longueur du conduit fournie est destinée à faciliter l'entretien du four. Ne pas couper le conduit. La boîte de jonction doit être située à 3" (7,6 cm) maximum sous la surface de support. Percer un trou de diamètre minimal de 1" (3,4 cm) dans le coin arrière droit ou arrière gauche de la surface de support pour accéder à la boîte de jonction.

REMARQUE : Pour une installation sous le comptoir, la boîte de jonction doit être située dans l'armoire adjacente droite ou gauche. Percer un trou de diamètre minimal de 1" (2,5 cm) dans un coin supérieur de la paroi latérale pour accéder à la boîte de jonction.

EXIGENCES D'INSTALLATION EN AFFLEUREMENT
Une profondeur minimale de l'ouverture de 21 7/8" (55,6 cm) est requise. Ces dimensions donneront un dégagement de 1/8" (0,3 cm) au sommet, un dégagement de 1/8" (0,3 cm) sur les côtés et un dégagement de 1/8" (0,3 cm) au bas du four à micro-ondes. Le côté avant des tasseaux et cales d'espacement sera visible et doit être traité comme une surface de finition.

EXIGENCES DE L'ARMOIRE
REMARQUE : En cas d'installation sous un comptoir, vérifier les spécifications du fabricant de l'armoire pour vérifier l'adaptation.

INSTALLATION SOUS COMPTOIR
(sans table de cuisson au-dessus)

VUE DU DESSUS

VUE ARRIÈRE

*Les tasseaux et les cales d'espacement doivent être encastrés à 13/16" (2,1 cm) depuis l'avant du placard.

IMPORTANT : Les spécifications dimensionnelles sont fournies uniquement à des fins de planification.
Ne faire aucune découpe sur la base de cette information. Se référer au guide d'installation avant de choisir une armoire, de vérifier les connexions électriques/gaz, d'effectuer des découpes ou de commencer l'installation. Tous les appareils JennAir® sont homologués UL, CUL ou CSA.

®/™ ©2019 JennAir. Tous droits réservés. Utilisé sous licence au Canada.

W11318378B
Instructions d'installation :
W11322487

Specification Sheet for Product:
JennAir JBRFR30IGX
Panel Ready 30 Inch Wide 17 Cu. Ft. Energy Star Rated All Fridge Right Swing Refrigerator

30" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JENNAIR®

JBRFR30IGX, JBRFL30IGX and ALOVE30RRC

29¾"(W) x 83⁷⁄₁₆"(H) x 23¹¹⁄₁₆"(Depth without door panels/handles)

Choose one of following configuration to match your kitchen design.

Base Unit (Panel Ready)	Base Unit+Stainless Panel Kits			
	RISE™ Stainless Panel	NOIR™ Stainless	Euro-Style Stainless Panel	Pro-Style® Stainless Steel Panel
Column refrigerator JBRFR30IGX, JBRFL30IGX, ALOVE30RRC	 LH: JKCPL301GL, RH: JKCPR301GL	 LH: JKCPL301GM, RH: JKCPR301GM	 LH: JKCPL301GS, RH: JKCPR301GS	 LH: JKCPL301GP, RH: JKCPR301GP

OPTIONAL ACCESSORIES FOR CUSTOM OVERLAY DESIGNS

RISE™ STAINLESS HANDLE KIT

- W11220303
- For use with Custom Overlay panels
- Quantity - One handle per kit

NOIR™ STAINLESS HANDLE KIT

- W11220302
- For use with Custom Overlay panels
- Quantity - One handle per kit

EURO-STYLE HANDLE KIT COLUMNS

- W11220300
- For use with Custom Overlay panels
- Quantity - One handle per kit

PRO-STYLE® HANDLE KIT COLUMNS

- W11220299
- For use with Custom Overlay panels
- Quantity - One handle per kit

JOIN KITS (FOR MULTIPLE UNIT INSTALLATIONS)

 Handle-to-handle join kit (JAJ13HSS)	 Handle-to-hinge join kit (JAJ11HSS)	 Hinge-to-handle join kit (JAJ12HSS)	 Burlesque Handle-to-handle join kit (JAJ14JSS)

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

W11356519A

30" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JENNAIR®

JBRFR30IGX, JBRFL30IGX and ALOVE30RRC

29¾"(W) x 83⁷⁄₁₆"(H) x 23¹¹⁄₁₆"(Depth without door panels/handles)

PRODUCT DIMENSIONS

*Add 1" (2.5 cm) to the height dimension when leveling legs are fully extended.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

30" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JENNAIR®

JBRFR30IGX, JBRFL30IGX and ALOVE30RRC

29¾"(W) x 83⁷⁄₁₆"(H) x 23¹¹⁄₁₆"(Depth without door panels/handles)

PRODUCT DIMENSIONS

FRONT VIEW

TOP VIEW

DIMENSION	DESCRIPTION	JBRFR30IGX, JBRFL30IGX, ALOVE30RRC
A	**Height of door handle** RISE™ Stainless	57¹⁵⁄₁₆" (147.2 cm)
	NOIR™ Stainless	40⅝" (103.2 cm)
	Euro-Style Stainless	50¹⁄₁₆" (127.1 cm)
	Pro-Style® Stainless	45⁹⁄₁₆" (115.7 cm)
	Custom panel (3/4" thick)	** **
B	**Height to top of door handle** RISE™ Stainless	70¾" (179.7 cm)
	NOIR™ Stainless	68¹¹⁄₁₆" (174.5 cm)
	Euro-Style Stainless	68⁵⁄₁₆" (173.4 cm)
	Pro-Style® Stainless	66¹⁄₁₆" (167.7 cm)
	Custom panel (3/4" thick)	** **
C	**Width from side of refrigerator to handle – door fully open 115°**	15½" (39.4 cm)
D	**Width from side of refrigerator to handle – door open 90°**	5" (12.7 cm)
E	**Depth with handle** RISE™ Stainless	26⅝" (67.7 cm)
	NOIR™ Stainless	26⁹⁄₁₆" (67.5 cm)
	Euro-Style Stainless	26⁹⁄₁₆" (67.4 cm)
	Pro-Style® Stainless	27⅛" (68.9 cm)
	Custom panel (3/4" thick)	** **

**For custom panel models, this depends on handle chosen.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

30" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JENNAIR®

JBRFR30IGX, JBRFL30IGX and ALOVE30RRC

29¾"(W) x 83⁷⁄₁₆"(H) x 23¹¹⁄₁₆"(Depth without door panels/handles)

OPENING DIMENSIONS

†Soffit not required for a single column install.
††24" with 24" trim kit.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

30" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JENNAIR®

JBRFR30IGX, JBRFL30IGX and ALOVE30RRC

29¾"(W) x 83⁷⁄₁₆"(H) x 23¹¹⁄₁₆"(Depth without door panels/handles)

water supply location
under unit
(accessible behind air grille)

TOP VIEW

water supply location behind unit
(also approved for electrical supply)

BACK VIEW

ELECTRICAL SUPPLY LOCATION

- Lighter yellow area indicates electrical supply located in a cabinet or accessible space above the unit opening.
- Power cord length is 9ft and originates from the front right corner of the unit.
- There is room for a surface mount electrical outlets within the top 3½" of the opening.
- Darker yellow area indicates the electrical supply location within the top of the opening.
- Outlet should be located near the center of the allowable area for easy connection and disconnection after installation.

WALL WATER SUPPLY LOCATIONS

- Water outlet area shown in blue.
- Water outlet area is also approved for the electrical outlet location.
- Outlet area width and height corresponds to a 3/4" deep recessed area found on the back of all unit.
- Targeting the left side of the allowable area allows for additional water line routing flexibility and easier water line management under the unit.

FLOOR WATER SUPPLY LOCATIONS

- Floor access is available through the open space behind the air grille.
- The area available is shown in blue and is limited in size by the compressor compartment on the right and leveling assembly on the left.
- The height of the open space above the access area is 11" high which makes drilling water lines access holes through floor after installation possible.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

30" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JENNAIR®

JBRFR30IGX, JBRFL30IGX and ALOVE30RRC

29¾"(W) x 83⁷⁄₁₆"(H) x 23¹¹⁄₁₆"(Depth without door panels/handles)

ELECTRICAL REQUIREMENTS

⚠WARNING

Electrical Shock Hazard

Plug into a grounded 3 prong outlet.

Do not remove ground prong.

Do not use an adapter.

Do not use an extension cord.

Failure to follow these instructions can result in death, fire, or electrical shock.

115 V, 60 Hz, AC only, 15 A or 20 A fused, grounded circuit is required. A dedicated circuit is recommended. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.

WATER PRESSURE REQUIREMENTS

A cold water supply with water pressure between 40 and 120 psi (207 kPa and 827 kPa) is required to operate the ice maker. Call a licensed, qualified plumber with any questions about the water pressure.

REVERSE OSMOSIS WATER SUPPLY

A reverse osmosis system may be used provided that the water pressure from the filtration system meets the required water pressure requirements.

JennAir® Columns feature an auto-bypass water filtration system. To use your product with a reverse osmosis water filtration system, simply remove the water filter from the product.

LOCATION REQUIREMENTS

⚠ WARNING

Explosion Hazard

Keep flammable materials and vapors, such as gasoline, away from refrigerator.

Failure to do so can result in death, explosion, or fire.

Floor must be able to support the product's total weight of more than 600 lb (272 kg), including the door panels and contents of the product. Flooring under product must be at the same level as the room. Face of cabinetry must be plumb.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

30" COLUMN REFRIGERATOR

DETAILED PLANNING DIMENSIONS GUIDE

JENNAIR®

JBRFR30IGX, JBRFL30IGX and ALOVE30RRC

29¾"(W) x 83⁷⁄₁₆"(H) x 23¹¹⁄₁₆"(Depth without door panels/handles)

FRONT VIEW

Thickness (B)	3/4" (1.9 cm) max.
Weight	60 lbs. (27.2 kg) max.
Height (C)	79⅞" (202.9 cm)

WOOD PANEL GUIDE

⚠CAUTION

Pinch Hazard

Installation of door panels with less than a ⅜" (0.95 cm) gap between the door panel and the adjacent cabinet increases the risk of potential pinching.

MODEL	FLUSH WIDTH (A)
30"	29¾" (75.6 cm)

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

W11356519A

®/™ ©2019 JennAir. All rights reserved.

07/19

Specification Sheet for Product:
JennAir JBZFL18IGX
Panel Ready 18 Inch Wide 8 Cu. Ft. Energy Star Rated All Freezer With Left Hinge Door Swing

JENN-AIR® DETAILED PLANNING DIMENSIONS

18" COLUMN FREEZER

(BASE UNIT REQUIRES SUITE-COORDINATING PANEL KIT OR CUSTOM PANELS AND HANDLES)

JBZFR18IGX, JBZFL18IGX – 17⅞" x 83⁷⁄₁₆" x 23⁴³⁄₆₄" (without door/handles)

PRODUCT DIMENSIONS

FRONT VIEW

TOP VIEW

MODEL #		JBZFR18IGX JBZFL18IGX	
		in	cm
A	Width of door	17¾	45.1
B	Overall width	17⅞	45.4
C	Height of door handle Pro-Style® Stainless	45³⁵⁄₆₄	115.7
	Euro-Style Stainless	50¹⁄₆₄	127.1
	Custom panel (¾"/1.9 cm)*	**	**
D	Height to top of door handle Pro-Style® Stainless	66¹⁄₆₄	167.7
	Euro-Style Stainless	68¹⁷⁄₆₄	173.4
	Custom panel (¾"/1.9 cm)*	**	**
E	Height of door	79⅞	202.9
F	Height of bottom grille	3³⁵⁄₆₄	9.0
G	Width of recessed freezer	17⁹⁄₁₆	44.6
H	Width from side of freezer to handle – door fully open 115° Pro-Style® Stainless	10⁴¹⁄₆₄	27
	Euro-Style Stainless	10⁹⁄₆₄	25.8
	Custom panel (¾"/1.9 cm)*	**	**
I	Width from side of freezer to handle – door open 90° Pro-Style® Stainless	4¹⁄₃₂	10.2
	Euro-Style Stainless	3⁷⁄₁₆	87.4
	Custom panel (¾"/1.9 cm)*	**	**
J	Depth without door panel kit	23⁴³⁄₆₄	60.1
K	Depth with door Pro-Style® Stainless	24½	62.2
	Euro-Style Stainless	24½	62.2
	Custom panel (¾"/1.9 cm)*	24½	62.2
L	Depth with handle Pro-Style® Stainless	27⅛	68.9
	Euro-Style Stainless	26¹⁷⁄₃₂	67.4
	Custom panel (¾"/1.9 cm)*	**	**
M	Depth with door open 90°	44⁷⁄₁₆	112.9

*Custom panels should not exceed ¾" (1.9 cm) thickness.
**For custom panel models, this depends on handle chosen.

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.

JENN-AIR®

18" COLUMN FREEZER

(BASE UNIT REQUIRES SUITE-COORDINATING PANEL KIT OR CUSTOM PANELS AND HANDLES)

JBZFR18IGX, JBZFL18IGX – 17⅞" x 83⁷⁄₁₆" x 23⁴³⁄₆₄" (without door/handles)

DIMENSIONS AS INSTALLED

SIDE VIEW

MODEL #		JBZFR18IGX JBZFL18IGX	
		in	cm
A*	Height of recessed freezer	83¹⁹⁄₆₄	211.6
B	Depth with door open 90° (min.)	44⁷⁄₁₆	112.9
C	Depth with handle (min.) Pro-Style® Stainless	27⅛	68.9
	Euro-Style Stainless	26¹⁷⁄₃₂	67.4
	Custom panel (¾"/1.9 cm)**	†	†
D	Depth with door (min.) Pro-Style® Stainless	24½	62.2
	Euro-Style Stainless	24½	62.2
	Custom panel (¾"/1.9 cm)**	24½	62.2
E	Depth without door panel kit (min.)	23⁴³⁄₆₄	60.1

*Add 1" (2.5 cm) to the height dimension when leveling legs are fully extended.

**Custom panels should not exceed ¾" (1.9 cm) thickness.

†For custom panel models, this depends on handle chosen.

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.

JENN-AIR®

18" COLUMN FREEZER

(BASE UNIT REQUIRES SUITE-COORDINATING PANEL KIT OR CUSTOM PANELS AND HANDLES)

JBZFR18IGX, JBZFL18IGX – 17⅞" x 83⁷⁄₁₆" x 23⁴³⁄₆₄" (without door/handles)

OPENING/CLEARANCE DIMENSIONS

FRONT VIEW

BACK VIEW

MODEL #		JBZFR18IGX JBZFL18IGX	
		in	cm
A	Width (min.)	18	45.7
B	Height (min.)	84	213.4
C*	Depth (min.)	25	63.5
D	Width of recommended electrical location	14	35.6
E	Height of recommended electrical location	6½	16.5
F	Height to recommended electrical location	4½	11.4
e	Recommended electrical connection location		
w	Recommended water connection location		

*A minimum 8" (20.3 cm) furniture return must extend behind the face of the cabinet on all sides.

ELECTRICAL REQUIREMENTS

115 volt, 60 Hz, AC only, 15- or 20-amp fused, grounded circuit is required. A dedicated circuit is recommended. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.

WATER PRESSURE REQUIREMENTS

A cold water supply with water pressure between 40 and 120 psi (207 and 827 kPa) is required to operate the ice maker. Call a licensed, qualified plumber with any questions about the water pressure.

Reverse Osmosis Water Supply

A reverse osmosis system may be used provided that the water pressure from the filtration system meets the required water pressure requirements.

Jenn-Air® Columns feature an auto-bypass water filtration system. To use your product with a reverse osmosis water filtration system, simply remove the water filter from the product.

LOCATION REQUIREMENTS

Floor must be able to support the product's total weight of more than 600 lb (272 kg), including the door panels and contents of the product. Flooring under product must be at the same level as the room. Face of cabinetry must be plumb.

IMPORTANT: Dimensional specifications are provided for planning purposes only.
Do not make any cutouts based on this information. Refer to the Installation or Use & Care Guide *before* selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.
All Jenn-Air® appliances are appropriately UL, CUL or CSA approved.

JENN-AIR®

Specification Sheet for Product:
U-Line UHWC124-IS01A
Panel Ready 1 Class 24 Inch Wide 48 Bottle Capacity Panel Ready Built-In / Free Standing Wine Cooler with LED Lighting

HWC124 • 24” Wine Refrigerator • 1 Class

Stainless Frame | Black Frame | Integrated Frame | Integrated Solid

Additional Options

- Stainless lock model available

Stainless Lock Model

Key Features

- Convection cooling system provides a quick cool down and consistent temperature
- Extended lower interior maximizes storage options
- Black interior
- LowE coated, argon gas filled, dual thermopane glass door provides protection from harmful UV Light
- Stainless steel full-wrap door and handle (⅞” diameter)
- Stainless steel grille (stainless model), black metal grille (black & integrated models)
- Five, three-quarter extension, black wine racks
- Digital touch pad control
- Temperature range: 34°F to 60°F
- Bright white LED lighting
- Volume of 5.5 cu ft holds up to 48 wine bottles (750 ml)
- Field reversible door is shipped right-hand hinged
- Integrated model requires ¾” custom door panel and handle (not supplied by U-Line)
- Built-in or freestanding
- Four adjustable leveling legs

Model Details

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
UHWC124-SG01A	115 / 60	Field Reversible	Stainless Frame	125 lb
UHWC124-SG31A	115 / 60	Field Reversible	Stainless Frame (Lock)	125 lb
UHWC124-IG01A	115 / 60	Field Reversible	Integrated Frame	115 lb
UHWC124-IS01A	115 / 60	Field Reversible	Integrated Solid	110 lb
UHWC124-BG01A	115 / 60	Field Reversible	Black Frame	125 lb

Front

Side

Top

Specifications

Model	HWC124
Amps: Running (115 v)	1.2 A
Capacity: Wine Bottle (750 ml)	48
Capacity: Volume (cu ft)	5.5
Dimensions: Product Depth	22 1⁄2" / 572 mm
Dimensions: Product Height	34 1⁄8" / 867 mm
Dimensions: Product Width	23 15⁄16" / 608 mm
ENERGY STAR (Glass)	No
ENERGY STAR (Solid)	Tier 3
Energy Consumption: Avg. Per Year	310 kWh
Panel Height	30 1⁄4" / 768 mm
Panel Thickness	3⁄4" / 20 mm
Panel Type	2 3⁄4" / 70 mm Frame or Solid Panel
Panel Width	23 3⁄4" / 603 mm
Refrigerant Type	R600a (1.34 oz)
Sabbath (Star K Certified)	Yes
Temperature Range	34°F to 60°F

Back

Cabinet Cut-Out

Warranty

- 1 Year (parts & labor) / 5 year sealed system (parts)

+ **Additional 1 Year (parts & labor) warranty at no cost with product registration**

See complete warranty for details

Installation Notes

- 24" cutout width sufficient if door protrudes beyond adjacent cabinetry
- No additional clearance is needed for ventilation
- Do not obstruct front grille air flow

Specification Sheet for Product:
Avallon ABR242SGRH
Stainless Steel 24 Inch Wide 140 Can Energy Efficient Beverage Center with LED Lighting, Double Pane Glass, Touch Control Panel and Right Swing Door

Specification Sheet

Model: ABR242SG

BEVERAGE REFRIGERATOR

24-Inch Single Zone Undercounter Beverage Refrigerator, Stainless Steel Door

Features

- 140-can capacity built-in low temp beverage refrigerator
- White, blue and amber interior LED lighting options
- Seamless, stainless steel trimmed glass door
- UV resistant glass door with low-e, double-panes and argon gas between the two panes
- Touch panel with digital controls
- Clear tempered glass shelves
- Added security with a door lock
- Sabbath mode

Warranty

- One (1) year parts and labor
- Five (5) years compressor (part only)

Model Details

Model	Voltage	Door Swing	Finish
ABR242SGLH	115V	Left Hinge	Stainless Steel
ABR242SGRH	115V	Right Hinge	Stainless Steel

Accessories

Model	Description	Finish
PCWRFILTER	Replacement Carbon Filter	Gray

Intertek

©2022 Ferguson Enterprises, LLC 0122 3534645

Exterior Dimensions

Interior Dimensions

Door Swing

Specifications

Model#	ABR242SG
Can Capacity (12 oz.)	140
Capacity (Volume)	5.65 cu ft
Product Depth	23-7/16"
Product Depth with Handle	25-1/4"
Product Height	34-1/8"
Product Width	23-13/16"
Product Weight	112 lbs.
Refrigerant Type	R600a
Temperature Range	34°F - 65°F
Power Cord Length	6'
Amps	1.5
Electric Supply	115 VAC, 60 Hz

Cutout dimensions

Note: Dimensions in parentheses are in millimeters.
Specifications are subject to change without notice.
Visit Avallon.com for the latest information.

©2022 Ferguson Enterprises, LLC 0122 3534645

Specification Sheet

Model: ABR242PRG

BEVERAGE REFRIGERATOR

24-Inch Single Zone Undercounter Beverage Refrigerator, Panel-Ready Door

Features

- 149-can capacity built-in low temp beverage refrigerator
- White, blue and amber interior LED lighting options
- UV-resistant glass door with low-e, double-panes and argon gas between the two panes
- Touch panel with digital controls
- Clear tempered glass shelves
- Added security with a door lock
- Sabbath mode

Please note: Panel-ready appliances are designed to utilize custom panels to match your cabinetry. The panel-ready finish option does not include the pictured wood paneling.

Warranty

- One (1) year parts and labor
- Five (5) years compressor (part only)

Model Details

Model	Voltage	Door Swing	Finish
ABR242PRGLH	115V	Left Hinge	Panel-Ready Door
ABR242PRGRH	115V	Right Hinge	Panel-Ready Door

Accessories

Model	Description	Finish
PCWRFILTER	Replacement Carbon Filter	Gray
HDLPRO	PRO Style Handle for Undercounter Models	Stainless Steel
ADKP48SS	Dual Kickplate (intended for side-by-side installations of two 24" models)	Stainless Steel

Exterior Dimensions

Interior Dimensions

Door Swing

Specifications

Model#	ABR242PRG
Can Capacity (12 oz.)	149
Capacity (Volume)	5.65 cu ft
Product Depth	23-5/8"
Product Depth with Handle	25-7/16"
Product Height	34-1/8"
Product Width	23-13/16"
Product Weight	110 lbs
Refrigerant Type	R600a
Temperature Range	34°F - 65°F
Power Cord Length	6'
Amps	1.5
Electric Supply	115 VAC, 60 Hz

Cutout dimensions

**with a 3/4" (25mm) custom panel*

Note: Dimensions in parentheses are in millimeters.
Specifications are subject to change without notice.
Visit Avallon.com for the latest information.

©2023 Ferguson Enterprises, LLC 0223 5022839

Specification Sheet

Model: ABR242PRS

BEVERAGE REFRIGERATOR

24-Inch Single Zone Undercounter Beverage Refrigerator, Solid Panel-Ready Door

Features

- 149-can capacity built-in low temp beverage refrigerator
- White, blue and amber interior LED lighting options
- Touch panel with digital controls
- Clear tempered glass shelves
- Added security with a door lock
- Sabbath mode

Please note: Panel-ready appliances are designed to utilize custom panels to match your cabinetry. The panel-ready finish option does not include the pictured wood paneling.

Warranty

- One (1) year parts and labor
- Five (5) years compressor (part only)

Model Details

Model	Voltage	Door Swing	Finish
ABR242PRSLH	115V	Left Hinge	Solid Panel-Ready Door
ABR242PRSRH	115V	Right Hinge	Solid Panel-Ready Door

Accessories

Model	Description	Finish
PCWRFILTER	Replacement Carbon Filter	Gray
HDLPRO	PRO Style Handle for Undercounter Models	Stainless Steel
ADKP48SS	Dual Kickplate (intended for side-by-side installations of two 24" models)	Stainless Steel

Intertek

Exterior Dimensions

Interior Dimensions

Door Swing

Specifications

Model#	ABR242PRS
Can Capacity (12 oz.)	149
Capacity (Volume)	5.65 cu ft
Product Depth	23-5/8"
Product Depth with Handle	25-7/16"
Product Height	34-1/8"
Product Width	23-13/16"
Product Weight	98 lbs
Refrigerant Type	R600a
Temperature Range	34°F - 65°F
Power Cord Length	6'
Amps	1.5
Electric Supply	115 VAC, 60 Hz

Cutout dimensions

**with a 3/4" (25mm) custom panel*

Note: Dimensions in parentheses are in millimeters.
Specifications are subject to change without notice.
Visit Avallon.com for the latest information.

©2023 Ferguson Enterprises, LLC 0223 5022839

Specification Sheet for Product:
Avallon ABR242PRGLH
Panel Ready Glass 24 Inch Wide 140 Can Energy Efficient Beverage Center with LED Lighting, Double Pane Glass, Touch Control Panel and Left Swing Door

Specification Sheet

Model: ABR242SG

BEVERAGE REFRIGERATOR

24-Inch Single Zone Undercounter Beverage Refrigerator, Stainless Steel Door

Features

- 140-can capacity built-in low temp beverage refrigerator
- White, blue and amber interior LED lighting options
- Seamless, stainless steel trimmed glass door
- UV resistant glass door with low-e, double-panes and argon gas between the two panes
- Touch panel with digital controls
- Clear tempered glass shelves
- Added security with a door lock
- Sabbath mode

Warranty

- One (1) year parts and labor
- Five (5) years compressor (part only)

Model Details

Model	Voltage	Door Swing	Finish
ABR242SGLH	115V	Left Hinge	Stainless Steel
ABR242SGRH	115V	Right Hinge	Stainless Steel

Accessories

Model	Description	Finish
PCWRFILTER	Replacement Carbon Filter	Gray

Intertek

©2022 Ferguson Enterprises, LLC 0122 3534645

Exterior Dimensions

Interior Dimensions

Door Swing

Specifications

Model#	ABR242SG
Can Capacity (12 oz.)	140
Capacity (Volume)	5.65 cu ft
Product Depth	23-7/16"
Product Depth with Handle	25-1/4"
Product Height	34-1/8"
Product Width	23-13/16"
Product Weight	112 lbs.
Refrigerant Type	R600a
Temperature Range	34°F - 65°F
Power Cord Length	6'
Amps	1.5
Electric Supply	115 VAC, 60 Hz

Cutout dimensions

Note: Dimensions in parentheses are in millimeters.
Specifications are subject to change without notice.
Visit Avallon.com for the latest information.

©2022 Ferguson Enterprises, LLC 0122 3534645

Specification Sheet

Model: ABR242PRG

BEVERAGE REFRIGERATOR

24-Inch Single Zone Undercounter Beverage Refrigerator, Panel-Ready Door

Features

- 149-can capacity built-in low temp beverage refrigerator
- White, blue and amber interior LED lighting options
- UV-resistant glass door with low-e, double-panes and argon gas between the two panes
- Touch panel with digital controls
- Clear tempered glass shelves
- Added security with a door lock
- Sabbath mode

Please note: Panel-ready appliances are designed to utilize custom panels to match your cabinetry. The panel-ready finish option does not include the pictured wood paneling.

Warranty

- One (1) year parts and labor
- Five (5) years compressor (part only)

Model Details

Model	Voltage	Door Swing	Finish
ABR242PRGLH	115V	Left Hinge	Panel-Ready Door
ABR242PRGRH	115V	Right Hinge	Panel-Ready Door

Accessories

Model	Description	Finish
PCWRFILTER	Replacement Carbon Filter	Gray
HDLPRO	PRO Style Handle for Undercounter Models	Stainless Steel
ADKP48SS	Dual Kickplate (intended for side-by-side installations of two 24" models)	Stainless Steel

Exterior Dimensions

Interior Dimensions

Door Swing

Specifications

Model#	ABR242PRG
Can Capacity (12 oz.)	149
Capacity (Volume)	5.65 cu ft
Product Depth	23-5/8"
Product Depth with Handle	25-7/16"
Product Height	34-1/8"
Product Width	23-13/16"
Product Weight	110 lbs
Refrigerant Type	R600a
Temperature Range	34°F - 65°F
Power Cord Length	6'
Amps	1.5
Electric Supply	115 VAC, 60 Hz

Cutout dimensions

**with a 3/4" (25mm) custom panel*

Note: Dimensions in parentheses are in millimeters.
Specifications are subject to change without notice.
Visit Avallon.com for the latest information.

©2023 Ferguson Enterprises, LLC 0223 5022839

Specification Sheet

Model: ABR242PRS

BEVERAGE REFRIGERATOR

24-Inch Single Zone Undercounter Beverage Refrigerator, Solid Panel-Ready Door

Features

- 149-can capacity built-in low temp beverage refrigerator
- White, blue and amber interior LED lighting options
- Touch panel with digital controls
- Clear tempered glass shelves
- Added security with a door lock
- Sabbath mode

Please note: Panel-ready appliances are designed to utilize custom panels to match your cabinetry. The panel-ready finish option does not include the pictured wood paneling.

Warranty

- One (1) year parts and labor
- Five (5) years compressor (part only)

Model Details

Model	Voltage	Door Swing	Finish
ABR242PRSLH	115V	Left Hinge	Solid Panel-Ready Door
ABR242PRSRH	115V	Right Hinge	Solid Panel-Ready Door

Accessories

Model	Description	Finish
PCWRFILTER	Replacement Carbon Filter	Gray
HDLPRO	PRO Style Handle for Undercounter Models	Stainless Steel
ADKP48SS	Dual Kickplate (intended for side-by-side installations of two 24" models)	Stainless Steel

Intertek

Exterior Dimensions

Interior Dimensions

Door Swing

Specifications

Model#	ABR242PRS
Can Capacity (12 oz.)	149
Capacity (Volume)	5.65 cu ft
Product Depth	23-5/8"
Product Depth with Handle	25-7/16"
Product Height	34-1/8"
Product Width	23-13/16"
Product Weight	98 lbs
Refrigerant Type	R600a
Temperature Range	34°F - 65°F
Power Cord Length	6'
Amps	1.5
Electric Supply	115 VAC, 60 Hz

Cutout dimensions

**with a 3/4" (25mm) custom panel*

Note: Dimensions in parentheses are in millimeters.
Specifications are subject to change without notice.
Visit Avallon.com for the latest information.

©2023 Ferguson Enterprises, LLC 0223 5022839